



- NOTE:
1. ALL MATERIAL TO BE T304 SS UNLESS OTHERWISE NOTED.
 2. TANK SHELL TO BE 11 GAUGE T304 SS WITH #4 INTERIOR AND 2B EXTERIOR FINISH.
 3. TANK TOP AND BOTTOM HEAD TO BE DISH 7 GAUGE T304 SS WITH #4 INTERIOR AND MIRROR EXTERIOR FINISH.

6	LEG	6 X 4" SCH40 SS PIPE LEG W BRACING
5	MANWAY	17" X 21" MANWAY W GRAB BAR & SAMPLE VALVE
4	AGITATOR SHAFT	2" SCH40
3	BAFFLE	1 X SIDEWALL BAFFLE
2	LIFT LUG	2 X LIFT LUG
1	MOTOR SUPPORT	3" SCH40
N7	AGITATOR ACCESS	4" TRI-CLAMP
N6	OUTLET	3" TRI-CLAMP
N5	PORT 1	2" TRI-CLAMP
N4	PORT 2	2" TRI-CLAMP
N3	CIP	1.5" X 3" TRI-CLAMP, DUAL T-BALL, REMOVABLE
N2	VENT	4" TRI-CLAMP, SCREEN & SHRROUD
N1	INLET	3" X 4" TRI-CLAMP, NO-FOAM, REMOVABLE
N8	PORT 3	2" TRI-CLAMP, 14WMP 1/2", AT 90 DEGREE

3000 GALLON